

TDS RECON



RUGGED AND WATERPROOF



LONG-LIFE BATTERY



WINDOWS MOBILE 5.0



VERSATILE CONFIGURATIONS

Next-generation Recon adds integrated wireless, more memory, plus Windows Mobile 5.0

The TDS Recon® handheld from Tripod Data Systems™ adds new capabilities to help you do even more in the field. Available integrated Bluetooth and 802.11g wireless keep you connected. Versatile Microsoft® Windows Mobile® 5.0 software runs thousands of applications. Plus, the Recon offers even more Flash memory: 128 MB on the Recon 200X and 256 MB on the Recon 400X.

Compact, lightweight and built tough

The compact Recon weighs just 17 ounces, yet its rugged design delivers reliable performance in the field. The Recon meets rigorous MIL-STD-810F military standard for drops, vibration, humidity, altitude and extreme temperatures. And with an IP67 rating, it's impervious to water and dust.

Built-in wireless, plus versatile CompactFlash options

With the Recon, it's easy to make connections in the field. Bluetooth wireless lets you connect to mobile peripherals without cables, while 802.11g wireless gives you access to local area networks, e-mail and the

Internet. What's more, two CompactFlash (CF) slots let you add GPS, digital cameras, bar code scanners and other devices.

Hard working, yet easy to use

The Recon features a high-performance 200 MHz or 400 MHz Intel XScale processor, an improved touchscreen and a new built-in microphone. Its long-life battery works all day without a recharge. And to keep your data safe, the Recon employs robust, custom designed, high-performance NAND Flash. Its Windows Mobile 5.0 software runs all the applications you use most, including your calendar, e-mail and Mobile versions of Word and Excel, plus PowerPoint.

You never want to compromise in your work. With the Recon, you don't have to.



www.OCRuggedLaptops.com
Toll Free: 1-866-511-6113

RECON SPECIFICATIONS

STANDARD FEATURES

Windows Mobile 5.0 (Premium edition)
200 MHz or 400 MHz Intel PXA255 XScale processor
64 MB high-speed SDRAM
128 MB or 256 MB nonvolatile Flash storage
Sunlight-readable color TFT display
Touchscreen
Rugged waterproof design
Integrated speaker and microphone
15 hours of continuous room-temperature operation with default settings
Optional integrated Bluetooth and 802.11g wireless capability

STANDARD SOFTWARE

Word Mobile
Excel Mobile
PowerPoint Mobile
Outlook Mobile
Internet Explorer Mobile
Contacts
Tasks
Notes
Calendar
Calculator
Windows Media Player
Microsoft Pictures and Videos
Microsoft ActiveSync
Microsoft Outlook 2002
Online help
Terminal services client

STANDARD ACCESSORIES

Rechargeable PowerBoot Module™
Standard CF-Cap™
AC charger
USB data cable
User's guide
Hand strap
Two stylus pens
Package of 10 screen protectors

OPTIONAL ACCESSORIES

Carry case
Deluxe case with belt clip and neck strap
Stylus lanyard
Serial interface cable

AA PowerBoot Module
Midsize CF-Cap
Extended CF-Cap
Optical CF-Cap
Tripod bracket, range pole bracket
12V vehicle charging cable
CompactFlash cards—GPS, bar code scanners, camera, 802.11 or Bluetooth
Vehicle mount
Desktop cradle

PHYSICAL

Size: 6.50" (16.5 cm) x 3.75" (9.5 cm) x 1.75" (4.5 cm)
Weight: 17 ounces (490 g) including rechargeable PowerBoot Module

ENVIRONMENT

Operating temperature: -22 to 140 °F (-30 to 60 °C)
Storage Temperature: -40 to 158 °F (-40 to 70 °C)
Temperature shock: MIL-STD-810F, Method 503.4
Humidity: MIL-STD-810F, Method 507.4
Water: IP67, sealed against accidental immersion (1 m for 30 min.) MIL-STD-810F, Method 512.4, Procedure I
Drop: MIL-STD-810F, Method 516.5, Procedure IV
26 drops from 4 ft (1.22 m) onto plywood over concrete, 6 additional drops at -22 °F (-30 °C), 6 additional drops at 140 °F (60 °C)
Sand and dust: IP67, MIL-STD-810F, Method 510.4, Procedure I

Vibration: MIL-STD-810F, Method 514.5, Procedure I (Fig. 17) & II

Altitude: MIL-STD-810F, Method 500.4, Procedures I, II & III 15,000 ft at 73 °F (23 °C)

ELECTRICAL

Processor: Intel PXA255 XScale CPU
200 MHz (Recon 200X)
400 MHz (Recon 400X)

Memory: 64 MB high-speed SDRAM
~22 MB reserved

Storage: Onboard nonvolatile NAND Flash
128 MB (Recon 200X)
256 MB (Recon 400X)
~31 MB reserved

Expansion: 1x Type I and 1x Type II
CompactFlash slots

Display: 240x320 pixel (1/4 VGA) color TFT with LED front light

Batteries: 3800 mAh NiMH rechargeable pack

I/O

Ports: 9-pin serial port—RS232 (115 Kbps)
USB client
DC power port



The 9-pin RS-232 serial and USB ports accept standard computer cables for maximum compatibility. And the Recon's internal components are fully sealed and protected in case of accidental immersion in water.



The Recon weighs 17 ounces and has rounded edges that fit comfortably in your hand. Optional modules include a AA PowerBoot Module and various CF-Caps that support larger accessories such as GPS receivers or bar code scanners.

©2006-2007 Tripod Data Systems, Inc. All rights reserved. Recon is a registered trademark of Tripod Data Systems. Tripod Data Systems, the TDS triangles logo, PowerBoot Module, AA PowerBoot Module, CF-Cap, Extended CF-Cap, and Optical CF-Cap are trademarks of Tripod Data Systems. Microsoft, Windows, and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Other brand names and trademarks are property of their respective owners. Color display images shown may vary slightly from actual display. Specifications subject to change.

OC Rugged Laptops & Mobile PCC, LLC
9877 Chapman Avenue Suite D-605
Garden Grove, CA 92841
Toll Free: 866-511-6113 Email: Info@OCRuggedLaptops.com
Fax: 714-638-5926 www.OCRuggedLaptops.com

YOUR LOCAL TDS DEALER

P.O. Box 947,
Corvallis, OR 97339

tdsway.com



NZ022490-015A