



GD6000®

High-Performance Vehicle-Rugged Notebook

WIRELESS

- Fully Mobile Platform with Integrated
 - 802.11a/g/n
 - GPS
 - Bluetooth
 - EVDO Rev A
 - HSDPA/UMTS
- Protected High Gain Antennas for Increased Coverage and Reliability

DURABLE

- Fully-Rugged Temperature Range
- Fully-Rugged Vibration Resistance
- Fully-Rugged Dust Ingress Protection
- Fully-Rugged Humidity Standard
- Best in Class Drop Protection
- Most Spill Resistant Keyboard

PERFORMANCE

- 13.3" DynaVue® *patent pending* Touchscreen Display
 - Better Viewability than 1,000 NIT Display
- Integrated Keyboard Task Lights
- Intel® 2.53GHz T9400 Core 2 Duo Processor
- 1066 MHz FSB
- Up to 4GB Memory
- 6MB L2 Cache
- Intel® GM45 Chip Set

SECURITY

- TPM v.1.2
- Integrated Fingerprint Reader
- Smartcard Reader for access "Gate Keeping"
- Removable Hard Disk Drive

Performance for the Office, Durability for the Road

Performance and durability come together in the GD6000 to create a notebook that is equally at home in the office and on the road.

Designed for mobile workforces, the GD6000 is the only notebook optimized for vehicle deployments. It meets fully-rugged standards for temperature, vibration, dust ingress and humidity. It can also survive punishing 30" drops and comes standard with a spill resistant keyboard, dual task lights and the industry's best 13.3" outdoor viewable touchscreen display featuring our *patent-pending* DynaVue® technology. And it has options for GPS, WWAN and a full function vehicle dock.

This best in class road durability does not come at the expense of office performance. The GD6000 is equipped with the Intel® Core™2 Duo T9400 processor, 1066 MHz FSB, 6MB L2 Cache, and up to 4GB of memory. An optional office dock, external keyboard, mouse and display make office work a breeze. For best in class durability, performance, and unparalleled outdoor viewability check out the GD6000 - it works where you work.



Product Specifications

Durability Features:

- Magnesium alloy housing
- Shock mounted HDD and display
- MIL STD 810F vibration, temperature range and humidity
- ANSI/IEC 529 IP 5x dust ingress protection
- Spill resistant keyboard and palm rest
- 30" drop protection

Software

- Microsoft® Windows® Vista
- Microsoft® Windows® XP

CPU:

- Intel® Core™2 Duo T9400
- 6MB L2 cache
- Processor speed 2.53 GHz (Dual Core)
- 1066MHz Front Side Bus

Storage & Memory:

- 1024MB SDRAM (DDR3) standard expandable to 4096MB
- 120GB 2.5" (6.35cm) 5400 RPM standard HDD
- Optional HDD heater for low temperature performance
- Multi Drive CD-RW/DVD-RW

Display:

- 13.3" 1024 x 768 (XGA) transmissive TFT Active Matrix Color LCD with touchscreen display
- Outdoor viewable with DynaVue® *patent-pending* display
- DynaVue® exceeds the minimum contrast ratio as required for bright sunlight per DOD-STD-3009
- External video support up to

2048 x 1536 at 16,777,216 colors

- Mobil Intel® GM45 Chipset, DVMT (Dynamic Video Memory Technology) resource allocated to 1024MB

Audio:

- Intel® High definition audio compliant
- Realtek ALC 269 CODEC
- Integrated stereo speakers
- Convenient keyboard volume and mute controls

Expansion Slots:

- PC Card type I or II x 1
- Optional Express Card x 1
- Optional SmartCard reader

Multimedia Pocket:

- Multi Drive (CD-RW/DVD-RW)

Keyboard & Input:

- 84-Key with dedicated Windows® key
- Full size 19mm pitch
- Electrostatic touchpad with scrolling support
- Touchscreen LCD
- Stylus

Interface:

- External Video - Mini-D-sub 15 pin
- Headphones/Speaker - Mini-jack stereo
- Microphone/Line in - Mini-jack stereo
- Port Replicator (Docking) - Dedicated 84 pin
- Serial - D-sub 9 pin
- USB 2.0 (x2) - 4 pin
- 10/100/1000 Ethernet - RJ-45

- V.92 56K BPS Modem - RJ-11

Power Supply:

- 6 cell high capacity lithium-Ion (47.5WH)
- AC Adapter: AC 100V-240V 50/60Hz, Auto Sensing/Switching
- Optional 9-cell high capacity Lithium-Ion (71.3WH)

Power Management:

- Hibernation, Standby, ACPI BIOS
- Power Saver power management software

Dimensions & Weight:

- 2.24" (H) x 12.05 (W) x 10.24" (D)
- 5.7cm (H) x 30.6cm (W) x 26 (D)
- 6.2 Lbs (2.81kg)

Security Features:

- Password Security; Supervisor, User
- Cable lock slot
- Trusted Platform Module Security Chip (TPM) v.1.2
- SuperPassword
- Pre-boot Password

Wireless:

- Wireless LAN 802.11a/g/n
- Intel® WiFi Link 5100 HMC Connection with respective drivers
- Radio on/off switch
- Security
 - Authentication, LEAP, WPA, 802.1x, EAP-TLS, EAP-FAST, PEAP
 - Encryption CKIP, TKIP, 128-bit and 64-bit WEP, Hardware AES
- Wide Area Wireless Solutions

(Common Radio Module Architecture)

- EVDO Rev A
- HSDPA
- GPS
 - Quadra-helix antenna for faster and more accurate fixes
 - High sensitivity SiRF III firmware and software
- Bluetooth® 2.0 +EDR
- Integrated and protected antennas

Warranty:

- 3-year limited warranty, parts & labor

Integrated Options:

- Express Cards Slot
- SmartCard Reader
- Fingerprint Reader
- Front or rear mount soft handle
- Rear mount hard handle
- Custom labels
- Custom color
- Custom Disk Image
- Shoulder Strap & Hardware Kit front or rear mount

Accessories:

- Vehicle Dock
- Vehicle Dock w/ external antenna connections for WLAN and WWAN
- Office Dock
- Standard Battery (6 cells)
- Extended Battery (9 cells)
- AC Adapter & Cord (65W)
- Vehicle Adapter 12V-18V (70W)
- Soft Handle & Hardware Kit
- Carry Cases

GENERAL DYNAMICS

Itronix

North America Head Office: 12825 E. Mirabeau Parkway • Spokane Valley, WA 99216 • Tel: +1-800-441-1309, +1-509-624-6600 • Fax: +1-509-626-4203 • Email: sales@itronix.com • www.gd-itronix.com
EMEA Head Office: Earlplace Business Park, Fletchamstead Highway, Coventry, CV4 9UR UK • Tel: +44(0) 24 7671 4800 • Fax: +44(0) 24 7671 5677 • Email: sales@gd-itronix.eu • www.gd-itronix.eu

Germany: Tel: +49 211 5 23 91 459 • Fax: +49 211 5 23 91 200 • Email: sales@gd-itronix.eu • www.gd-itronix.eu

France: Parc d'Affaires Siic, 74 Rue d'Arcueil, BP 10405, 94573 RUNGIS Cedex, France • Tel: +33(0) 1 46 87 80 09 • Fax: +33(0) 1 45 60 55 95 • Email: sales@gd-itronix.eu • www.gd-itronix.eu

Canada: 2783 Thamesgate Dr., Mississauga, Ontario, L4T 1G5, Canada • Tel: +1-800-571-5434 • +1-905-672-7007 • Fax: 1-905-672-3999 • Email: sales@itronix.com • www.gd-itronix.com

Asia: 2nd Floor, No 88, Chung-Hsiao East Road Sec. 2 Taipei 100, Taiwan • Tel: +866 2 2393 0660 • Fax: +886 2 2395 5256 • Email: sales@itronix.com.tw

© 2008 General Dynamics. All rights reserved. General Dynamics Itronix Corporation reserves the right to make changes in its products and specifications at any time and without notice. All trademarks indicated as such herein are trademarks of General Dynamics Itronix. All other product and service names are the property of their respective owners. © Reg. U.S. Pat. and Tm. Off. V.2 11/08